

NORSHIELD

ASSA ABLOY

Experience a safer
and more open world

SDR MAX SECURITY DOOR

Murfreesboro Police Department—Murfreesboro, Tennessee

Architect: Architect Workshop

The all-new SDR Max

UNDERSTATED HIGH SECURITY

- **Smooth, dependable, high-security protection.** Door is locked and deadlocked upon closing, ready to protect from forced entry, ballistic or blast threats.
- **Multipoint auto-lock.** Secures automatically when closed (no manually operated forced entry locks).
- **Fully mortised multipoint lock** which provides a clean, sleek door design with no exposed locks or locking mechanisms.
- **Available with all typical hardware functions.** Panic bar, exterior cylinder, lever actuation (interior and/or exterior), combination lock, ADA compliant, local and remote electric actuation options.
- **Single point lock retraction & deadlock from threat side** (eliminates multiple cylinders and thumbturns).
- **Available as out-swing and in-swing** configurations; singles or pairs.
- **Blast resistant design** meets requirements for both positive and negative pressure (rebound) protection during a blast event. (GSA, DOD & DOS)
- **Tested to SD-STD-01.01;** Rev G high power rifle, (15 & 60 minute) forced entry. DS certified to Rev H rifle ballistics, (5, 15 & 60-minute) forced entry.
- **Tested to ASTM F3038-14** (5, 15, 30 & 60 minute)
- **Tested to multiple ballistic standards** including; DOS Rifle & AP, UL752 Rifle (Levels 4, 5, 7, 8 & 9), ASTM F1233 (R1, R2, R3 & R4), NIJ (Level III and Level IV) and BS EN 1522/1523 (BR6).

SDR MAX-OP



U.S. Patent
No. 11,725,421

The ASSA ABLOY Group is the global leader in access solutions. Every day we help people feel safe, secure and experience a more open world.

Series SDR MAX & SDDR MAX

Industry-leading security features and unmatched design flexibility.



SDR MAX-HV

U.S. Patent
No. 11,725,421



Adjustable
Mechanical
Trigger at top
of door leaf




1" throw with
available
mechanical
interlock to
prevent single
motion retraction
of latches




Armored
exterior key
cylinder for
manual entry




Robust cast
and machined
components with
rack and pinion
mechanism
ensures long-
term reliability
and consistent
function.




SDDR MAX-DV




SDDR MAX-FV




SDDR MAX-HV




SDDR MAX-TW




SDDR MAX-VL




SDDR MAX-NL




SDDR MAX-OP




SDR MAX-FV




SDR MAX-HV




SDR MAX-TW




SDDR MAX-DV




SDDR MAX-VL



SDR MAX-NL



SDR MAX-OP

BALLISTIC RATINGS						FORCED ENTRY RATINGS						
SDR MAX & SDDR MAX												
DOS SD-STD 01.01	REV G RIFLE		REV G AP		REV H RIFLE		DOS SD-STD-01.01	REVISION G				
	7.62/5.56 - 3 SHOTS		.30 CAL AP - 1 SHOT		7.62/5.56 - 3-8 SHOTS			5 MINUTE	15 MINUTE	60 MINUTE		
UL 752	3	4	5	7	8	9	DOS SD-STD-01.01	REVISION H				
	.44 MAG 3 SHOTS	.30-06 1 SHOT	7.62 MM 5 SHOTS	5.56 MM 5 SHOTS	7.62 MM 5 SHOTS	.30 CAL AP 1 SHOTV		5 MINUTE	15 MINUTE	60 MINUTE		
NIJ 0108.1	IIIA		III		IV		ASTM F3038	5	15	30	60	
	.44 MAG - 5 SHOTS		7.62 MM - 5 SHOTS		.30 CAL AP - 1 SHOT			5 MINUTE	15 MINUTE	30 MINUTE	60 MINUTE	
ASTM F1233	R1		R2		R3		FIRE RATINGS – COMING SOON					
	5.56 mm 3 Shots		.30-06 3 Shots		7.62 mm 3 Shots							.30 Cal AP 1 Shot
EN 1522/1523	BR6				BR7				<div></div> <div>Scan for more details on this and other Norshield products.</div>			
	7.62/5.56 - 3 SHOTS				.30 CAL AP - 3 SHOTS							